

Product Information Sheet

Honeywell Whiting + Davis

Stainless Steel Mesh Gloves



| Part Number | Size | Strap Color | Glove Weight | UPC |
|-------------|---------|-------------|--------------|--------------|
| A515XXS D | XXSmall | Yellow | .421 | 801462012897 |
| A515XS D | XSmall | Gray | .445 | 801462012804 |
| A515S D | Small | White | .493 | 801462012705 |
| A515M D | Medium | Red | .555 | 801462012651 |
| A515L D | Large | Blue | .581 | 801462012606 |
| A515XLD | XLarge | Green | .609 | 801462012750 |
| A515XXL D | XXLarge | Brown | .620 | 801462012859 |

Product Features

- Five finger mesh glove, side cuff slit for easy donning and doffing of glove
- Individually welded stainless steel rings
- Gloves are 4-ring joined at the seams to prevent gaps and knife sticks
- Thumbs are attached with 3 ring join, for the strongest seam at a high wear area
- Ergonomic design is comfortable to wear and diminishes sagging mesh
- Gloves are ambidextrous following the 3 Step Reversible Design



| Stainless Steel Ring Data | |
|---------------------------|--------------|
| SS Material | 316 |
| Wire Diameter | .0197 inches |
| Ring Outside Diameter | .157 inches |
| Ring Inside Diameter | .118 inches |

Testing Information

Whiting + Davis products are not CE certified, but are manufactured following the European Standard of EN1082; section 6.4.1 states: "Smoothly and progressively apply a force that pulls the rings apart as it rises from 0 N to 100 N (22½ pounds of force) over a period of 2 to 10 seconds. Report all instances of rings or plates opening or breaking at a force of below 100 N." *N(Newton) = .225 pounds of force Whiting+ Davis products, and Whiting + Davis products manufactured by Chainex have always exceeded the European Standard.

Laundering Instructions

Metal mesh gloves and garments should be cleaned and sanitized at least once daily, particularly in food processing and food handling operations to comply with regulations governing these industries. This can be accomplished by using a mild detergent in clean, warm water and vigorously scrubbing gloves to remove foreign matter. The gloves can also be laundered in washing machine, again using a mild detergent. Water temperature of 122° F (50° C) is recommended whether gloves are manually or machine washed.

After washing, gloves must be rinsed in clean, hot water, at least 180°F (82° C). Only disinfectants approved by food hygiene authorities should be used. After gloves have been cleaned and rinsed, store in a cool, dry and well ventilated area. The practice of hitting gloves against work stations or hard surfaces of any kind to remove debris is specifically discouraged, as such repetitive action could damage the mesh.

Warnings

* Gloves are cut-resistant, not cut proof. Extreme caution should be used around moving machinery.

** Laundering gloves that have been in contact with toxic or corrosive chemicals may result in a chemical reaction, including fumes that could cause personal injury, serious illness or death.

This information is provided as a guideline for product use. The end user is solely responsible for determining the suitability of a particular glove for a specific application and the length of time in which such glove may be safely used.

Honeywell Industrial Safety

900 Douglas Pike
Smithfield, RI02917

U.S.A
Tel: 800.430.5490
Fax: 800.322.1330

Canada
Tel: 888.212.7233
Fax: 888.667.8477