



# HAND PROTECTION

## Performance Chemical, Cut, Abrasion, and Puncture Resistant Gloves

### DESCRIPTION

These 12-inch long double-dipped on PVC and nitrile gloves feature a seamless, 15-gauge Aralene® (enhanced aramid fiber) cut resistant liner. These chemical handling gloves are enhanced with a sandpaper grip dipped palm for extended wear resistance. Nitrile provides chemical resistance and when blended with 70% PVC offers additional flexibility.

### INDUSTRY

Light Metal Fabrication	Handling Oily Components
Parts Handling	Maintenance
Chemical Handling	



### FEATURES

- 15-gauge Aralene® sewn liner offers cut and high temperature resistance
- Premium 30% nitrile and 70% PVC blended shell
- Sandpaper finish enhances grip in wet or oily situations
- 12-inch length for extra arm protection
- Overcast color on hem for easy size identification
- Gauntlet cuff allows for easy donning and removal plus extra forearm protection
- ANSI/ISEA 105 Cut Level A3
- ASTM F2992-15 Results = 1,357 grams

### ITEM CR292

- ANSI/ISEA 105 Abrasion Level 5
- ANSI/ISEA 105 Puncture Level 2
- ANSI/ISEA 105 Puncture Results: 43 Newtons
- EN 388 Levels: 3X31C
- EN 374 Levels: AJKL
- EN 407 Levels: X1XXXX

### SIZES 8(M)-10(XL)



### SPECIFICATIONS

LINER	GAUGE	COATING	COATING COLOR	COATING TYPE	FINISH	CUFF	CUFF COLOR
Aralene®	15-Gauge	PVC/Nitrile	Black	Double-Dipped	Sandpaper	Gauntlet	Green
ANSI CUT	ASTM F2992-15 RESULTS	ANSI ABRASION	ANSI PUNCTURE	PUNCTURE RESULTS	EN 388 LEVELS	EN 374 LEVELS	EN 407 LEVELS
Level A3	1,357 Grams	Level 5	Level 2	43 Newtons	3X31C	AJKL	X1XXXX

### PACKAGING

	QUANTITY	8(M)	9(L)	10(XL)
PAIR UPC	1	N/A	N/A	N/A
INNER PACK UPC	12/PACK	810292029364	810292029374	810292029388
CASE GTIN	6 PK/CASE	10810292029361	10810292029378	10810292029385
CASE WEIGHT (IN POUNDS)		31	33	35
OVERCAST COLOR		Green	Brown	Black

13915 Radium St NW  
Ramsey, MN 55303

763-450-0110  
Sales@GlobalGlove.com

GlobalGlove.com

  
**Global Glove**  
& Safety Manufacturing, Inc.